Amphenol Sensors

Connecting your world through Sensing Innovations

HVAC for Medical Facilities

Amphenol Sensors is a leading innovator in sensing technologies and measurement solutions. Offering the most diverse sensor portfolio of standard and customized products for the world's most demanding regulatory and industry-driven applications, Amphenol creates value by providing critical information for real-time decisions.

The demands of today's healthcare industry require not only the highest criteria in the direct care of a patient, but also the highest quality, accuracy and efficiency in those facilities that allow for that care.

Within a medical facility, the proper operation of its heating, ventilating and air conditioning (HVAC) systems also ensures proper operation of various medical support functions to provide for the health, comfort and safety of that facility's occupants, including patients, visitors and staff.

Amphenol Sensors' diverse portfolio of world class sensing solutions touches nearly every facet of a medical facility's HVAC systems to ensure not only the utmost in conditions for patient care and recovery, but also long-term efficiency to achieve green building status.



Amphenol Sensors

HVAC for Medical Facilities

Application		Solution	Technology & Features						
Carbon Dioxide (CO ₂)	Fresh Air Ventilation Control	Monitors patient/staff occupancy to ensure proper CO ₂ levels For use in temporary medical facilities with no standard Building Automation System (BAS) in place	Dual channel automatic calibration Outputs: 0-10v, 0-5v, 4-20mA, relay, BACnet						
Oxygen	Inline Oxygen Measurement	Aids patient breathing in ventilator equipment	0-100% Volume Oxygen Wide pressure range Realtime measurements Linear Low power electrochemical sensor						
Humidity	Humidity Control	Prevents condensation that can cause mold growth, in addition to harmful respiratory conditions Ensures human comfort and energy efficiency	Accuracy Options: 2%, 3%, 5% Outputs: 0-10v, 0-5v, 4-20mA Field replaceable Relative Humidity (RH) sensor						
Pressure	Differential Pressure	Negative-pressure patient isolation room monitoring	Outputs: 0-10v, 0-5v, 4-20mA Range: 0-0.3"WC T30 Range: 0-0.5"WC, T10, T20 Piezoresistive sensor Offsets: 0, ¼, ½ span Units: In. WC, Pa, or mm H ₂ O Accuracy: ±1% of span						
	Measurement	Negative-pressure patient isolation room monitoring Fan/filter monitoring Sensing components for ventilators, sleep apnea, and oxygen concentrators	±0.5" H ₂ O and above High volume Accuracy: ±1.5 % of span						
	Climate Control Systems	Measures coolant pressure in HVAC systems	Stainless steel pressure sensing element, aluminum housing, RD-connector Pressure Range: -1-10bar to -1-100bar, gauge Temperature Range: -40°C to 125°C (150°C) Outputs: LIN, PWM, analog voltage						
	HVAC Refrigerant	Measures low and high pressures of HVAC refrigerant	Stainless steel, media-isolated 3psi – 7500psi Gauge, sealed and absolute piezoresistive transducers Output Options: 5V, 4-20mA, 4.5V Accuracy: 1% Variety of ports Harness accessories available						

Ap	plication	Solution	Technology & Features						
Combined Pressure & Temperature	Climate Control Systems	Measures pressure and temperature of coolants in HVAC systems	Compatible to all currently used coolants (R134a, R1234yf, R744) High temperature accuracy and fast response time Stainless steel pressure sensing element, aluminum or steel housing, RD-connector or MQS-connector Pressure Range: -1-10bar to -1-200bar, gauge Temperature Range: -40°C to 125°C (150°C) Output: LIN	(125 Le Americal Company)					
	Equipment Temperature Conditions	Monitors critical equipment for over-temperature conditions	 Sensing element isolated from tag Dielectric 750 Vac Eyelets to fit M3/M4/M5 screw sizes; additional diameters available Suitable for surface temperature measurement 	THERMOMETRICS					
	W To		 Configuration: Pipe Clip Designed for 250,000 thermal cycles between 25°C to 85°C Pipe Diameter Range: 13-30 mm (1/2-1-1/8 in) 	THERMOMETRICS					
<u>a.</u>	HVAC Systems Temperature	Provides temperature control for nearly every aspect of a medical facility, from maintaining the air temperature in an operating room	 Configuration: Integrated Pipe Clip IP57 Ingression Protection Rating AEC Q200 REV (D) - pending Sensing Element: Dielectric 750 Vac Pipe Diameter Range: 15-18 mm (5/8-1 in) Self-adjusts to irregular pipe surfaces 	THERMOMETRICS					
Temperature		to monitoring hot water temperature supplied to restroom sinks	 Configuration: Boiler Probe Connector Series: Molex Minifit Full range of TCO temperature ratings according to EN60691 Range of connectors available 	THERMOMETRICS					
			 Configuration: Cable Probe IP66 Rating Long-term stability Good thermal response time 	THERMOMETRICS					
	Floor Heating	Provides uniform temperature for in-floor heating	 Various resistance values available Various lead lengths available 	THERMOMETRICS					
	Air Conditioning	Directly measures object temperature for automatic adjustments	 Auto control of fan and blowing rate Long detection range (~5M) 	THERMOMETRICS					
	Medical Equipment	Provides position feedback for respiratory devices, infusion pumps, and electrophoresis devices	Programmable measuring angle with built-in redundancy Truly contactless operation with no wear; maintenance free Immunity to dust, moisture, vibration	PIHER sensing systems					
Position	Hospital Beds and Wheelchairs	Provides rotary angle/position feedback for power beds and power wheelchairs	 and extreme temperatures Robust, compact, and low profile up to IP69K Protection Absolute position feedback; position is not lost even on power loss High resolution up to 14-bit 	PIHER sensing systems					
	HMI Controls	Provides linear and rotary position sensing for centrifugators, X-ray and imaging systems, ventilators, patient monitor equipment, and HVACR	Low profile Long life Excellent resolution and linearity	PIHER sensing					

Sensing Technologies												
MAJOR MARKETS SERVED	Thermometrics, Inc. Temperature	Telaire Gas & Moisture	NovaSensor Pressure	Protimeter Moisture Meters	Kaye Thermal Validation	SGX Sensortech Gas	Piher Sensing Systems Position	Wilcoxon Sensing Technologies Vibration	Piezo Technologies Ultrasonic	i2s Pressure & Temperature	All Sensors Ultra Low Pressure	SSI Technologies Level, Quality & Pressure
Aerospace (Commercial)	•		•			•	•				•	•
Agriculture	•	•		•		•	•			•		•
Air Quality		•		•		•					•	•
Automotive	•	•	•			•	•			•		•
Automation	•	•					•	•			•	
Construction & Restoration				•								•
Electrification (EV/HEV)	•	•	•			•	•			•		•
Energy	•					•		•	•			
Environmental Monitoring					•	•					•	
HVAC - Industrial	•	•	•			•	•	•		•	•	•
HVAC - Medical Facilities												
Air-Conditioning	•	_										
Climate Control Systems												
Differential Pressure Measurement			•								•	•
Equipment Conditions												
Floor Heating												
Fresh Air Ventilation Control												
HMI Controls							•					
Hospital Beds and Wheelchairs												
Humidity Control		•										
HVAC Refrigerant												
HVAC Systems	•									•		
Inline Oxygen Measurement												
Medical Equipment							•					
Industrial	•	•	•	•		•	•	•		•	•	•
Marine												
Medical									•			
Military						•						
Non-Destructive Testing (NDT)												
Oil & Gas	•		•			•	•	•	•		•	•
Pharmaceutical & Biotech					•							•
Railway	•							•				•
Thermal Validation					•							



www.amphenolsensors.com

 $\ensuremath{\mathbb{O}}$ 2020 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice.

Other company names and product names used in this document are the registered trademarks of their respective owners.